

TRAILER PM / ANNUAL INSPECTION

Date: _____ Vehicle ID #: _____ Mileage: _____
 License Plate #: _____ Branch: _____
 Mechanic/Inspector: _____ Vendor: _____
 Address: _____ (Street Address) _____ (City) _____ (State) _____ (Zip)
 This Inspector meets the qualification requirements in Section 396.19 Yes Inspector Qualifications
 This Inspector meets the qualification requirements in Section 396.25 Yes Brake Qualification

- *Trailer B-PM Service must be completed every 180 days and includes greasing the trailer.
- * Trailer C-PM includes the federal annual inspection that must be completed every 12 months.
- * **Repair Codes: L= Lubricated R Repairs Needed A= Adjusted or Replaced X= Serviceable**

Trailer B-PM Instructions:	Repair Code:
1. Registration and Inspection: Check registration and license plates for validity. Check Federal Annual Inspection Decal for expiration date. Check condition of registration holder. *Report missing or expired registration.	<input type="checkbox"/> _____
2. Body Inspection: Check the header board for cracks or damage. Check the fifth wheel plate and king-pin for wear or cracks. Check the floor boards, side rails, ICC bumper, mud flaps, placards, rear door, rear rollers, and door hinges.	<input type="checkbox"/> _____
3. Frame Inspection: Check all cross members, sub-frames, sliding axel assemblies, gussets, and slide locks for cracks, excessive play, or heavy rust. Inspect Moffett mounting kit if installed. * Grease and inspect landing gear system.	<input type="checkbox"/> _____
4. Rear Coupler Inspection: Check the pintle hook, D-Rings, glad hands, shut off valves, and inspect light cord receptacle, front draw bars, draw bar eyes, and saddle mounts. * Lubricate pintle hook locks with spray lube.	<input type="checkbox"/> _____
5. Suspension: Check for broken springs, loose or broken U-Bolts, loose or worn torque arms, loose or cracked saddles and spring hangers, worn equalizer bushings, air bag damage, and air bag leveling valves. *Torque U-Bolts if found to be loose.	<input type="checkbox"/> _____
6. Inspect Brakes: All brake shoes must be free of cracks, oil contamination, and at least 1/4" lining minimum. Check brake chambers, brake valves, and air tanks. * Check brake adjuster travel with air applied. Use DOT allowable travel guidelines. * Grease the S-Cam bushings and slack adjusters for each wheel.	<input type="checkbox"/> _____
7. Wheels and Hubs: Check for wheel seal leaks. Check for cracked spokes or hubs, check wheels for loose lug nuts (torque wheel lug nuts if they are loose). * Check and fill oil hub caps. *Replace any leaking oil hub caps.	<input type="checkbox"/> _____
8. Tires: Inspect all tires for side wall damage, proper inflation, nails in the tread, and tread wear. Record tread wear on PM sheet. Remove tires at 2/32" tread. * Inflate all tires to the tire pressure indicated on the sidewall of each tire.	<input type="checkbox"/> _____
9. Lights and Reflectors: Check all tail lights, marker lights, turn signals, and reflective tape. Inspect light cord receptacles, wiring junction boxes, and wiring. * Repair all lights and replace missing reflective tape.	<input type="checkbox"/> _____
10. Install a PM Decal: Next to the registration holder and include the new date of the B-PM. * Attach this PM sheet to invoice for payment. * Report major defects to the fleet department.	<input type="checkbox"/> _____

Trailer C-PM Instructions:	Repair Code
1. Complete all of the B-PM Service Items: Repair all safety related defects found during B-PM. Report major defects to Fleet department.	<input type="checkbox"/>
2. Federal Annual Inspection requirements listed on the back of this PM form must be met to pass federal Annual C-PM Inspection.	<input type="checkbox"/>
3. Install Federal Annual Inspection decal on the trailer head board near the registration holder. * Remove all expired Federal Annual Inspection Decals.	<input type="checkbox"/>
4. Attach this PM sheet to invoice for payment and install the Manila copy in the registration holder	<input type="checkbox"/>
Brake Lining Remaining: List brake lining as: New, 3/4", 1/2", 3/8", or 1/4" thick Left Front: _____ Right Front: _____ Left Rear: _____ Right Rear: _____	

Front Trailer Axel			
LEFT		RIGHT	
32	32	32	32
Tire Tread:			
32	32	32	32
LEFT		RIGHT	
Rear Trailer Axel			

Repairs Needed: _____

Mechanic's Signature: _____

Print Name: _____

Certification: This vehicle has passed all the inspection items for the annual vehicle inspection in accordance with 49 CFR 396: YES NO